

EAP380-E

SMB Smart Indoor 802.11ac wave2 Dual Band AP

Product Overview

DCN EAP380-E is a wireless access point (AP) designed for the SMB market. It provides comprehensive service support capabilities and features high reliability, high security, simple network deployment, automatic AC discovery and configuration, and real time management and maintenance, which meets easy network deployment requirements. The AP complies 802.11ac wave 2 standards compliance and can offer maximum 1.167Gbps throughput – 300Mbps in 2.4G with 2x2, 867Mbps in 5G with 2x2. The EAP380-E is applicable to commercial chains, medical, warehousing and manufacturing environment.



802.11a/b/g/n/ac wave2



1167Mbps, 2*2 MIMO



concurrent user 100



Small office



Standard PoE Input



cloud management

Key Features and Highlights

High-speed wireless broadband access

The EAP380-E supports the 802.11a/b/g/n/ac wave2 standard, operates in 2.4 GHz and 5 GHz both bands, and provides an access bandwidth up to 1167 Mbps. MU-MIMO technology could support 2 terminals' communication simultaneously. Whole AP supports 3 terminals simultaneously, improving the overall throughput of the Wi-Fi network.

Flexible mounting

EAP380-E can support wall mounting, ceiling mounting, you can deploy it according to the actual environment.

Cloud management

EAP380-E can operate with the DCN cloud platform seamlessly to provide a better cost-performance solution; it can help SMB customers enjoy the stable

wireless connection at a lower cost.

Good PoE compatibility

EAP380-E can work well with all PoE switch (cisco, HUAWEI, etc.) which support 802.3af standard, this allows to power up EAP380-E directly, a power adapter is not required anymore.

Support WDS mode

EAP380-E can support WDS mode under both fits/fat AP mode. Use 2.4GHz and 5GHz to achieve wireless bridging function.

Dual-mode fit & fat

EAP380-E can work in fit or fat mode and can flexibly switch between the fit mode and the fat mode according to network planning requirements.

Product Specifications

Hardware Specifications

Item	EAP380-E
Dimension(L*W*D) (mm)	160 × 160 × 30
10/100 /1000Base-T port	1
Console port (RJ-45)	N/A
Power input	802.3af or 48V DC adapter
Maximum power consumption	<10W
RF port	Built-in 2.4 GHz 4 dBi antenna and 5 GHz 5 dBi antenna
Working frequency band	802.11a/n: 5.150 GHz to 5.850 GHz 802.11b/g/n: 2.4 GHz to 2.483 GHz 802.11ac: 5.150GHz to 5.250GHz 5.250GHz to 5.350GHz 5.725GHz to 5.850GHz
Modulation technology	802.11b: BPSK, QPSK, CCK 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
Transmit power	2.4G: 23dBm (Per Chain) 5G: 23dBm (Per Chain) (Note :final output power comply with deployment regulation might be different)
Power adjustment granularity	1 dBm
Working/Storage temperature	-0°C to +50°C -40°C to +70°C
Working/Storage RH	5% to 95% (non-condensing)
Protection level	IP31

Software Specifications

Item	Feature	EAP380-E
WLAN	Product positioning	Indoor dual-band
	Working frequency band	2.4 GHz and 5 GHz
	Bandwidth performance	1167Mbps
	Virtual AP (BSSID)	32
	Concurrent user	100
	Number of spatial streams	2.4G: 2 5G:2
	Dynamic channel adjustment (DCA)	Yes
	Transmit power control (TPC)	Yes
	Blind area detection and repair	Yes
	SSID hiding	Yes
	RTS/CTS	Yes
	RF environment scanning	Yes
	Hybrid access	Yes
	Restriction on the number of access	Yes
	Link integrity check	Yes
	Intelligent control of terminals based on airtime fairness	Yes
High-density application optimization	Yes	
11n enhancements	40 MHz bundling	Yes
	300 Mbps (PHY)	Yes
	Frame aggregation (A-MPDU)	Yes
	Maximum likelihood demodulation (MLD)	Yes
	Transmit beamforming (TxBF)	Yes
	Maximum ratio combining (MRC)	Yes
	Space-time block coding (STBC)	Yes
	Low-density parity-check code (LDPC)	Yes
Security	Encryption	64/128 WEP, TKIP, and CCMP encryption
	802.11i	Yes
	WAPI	Yes
	MAC address authentication	Yes
	LDAP authentication	Yes
	PEAP authentication	Yes
	WIDS/WIPS	Yes
	Protection against DoS attacks	Anti-DoS for wireless management packets
	Forwarding security	Frame filtering, white list, static blacklist, and dynamic blacklist
	User isolation	AP L2 forwarding suppression Isolation between client

Item	Feature	EAP380-E
	Periodic SSID enabling and disabling	Yes
	Access control of free resources	Yes
	Wireless SAVI	Yes
	ACL	Access control of various data packets such as MAC, IPv4, and IPv6 packets
	Secure access control of APs	Secure access control of APs, such as MAC authentication, password authentication, or digital certificate authentication between an AP and an AC
Forwarding	IP address setting	Static IP address configuration or dynamic DHCP address allocation
	IPv6 forwarding	Yes
	IPv6 portal	Yes
	Local forwarding	Yes
	Multicast	IGMP snooping
	Roaming	Yes
	AP switching reference	Signal strength, bit error rate, RSSI, S/N, whether neighboring APs are normally operating, etc.
	WDS	Yes
QoS	WMM	Yes
	Priority mapping	Ethernet port 802.1P identification and marking Mapping from wireless priorities to wired priorities
	QoS policy mapping	Mapping of different SSIDs/VLANs to different QoS policies Mapping of data streams that match with different packet fields to different QoS policies
	L2-L4 packet filtering and flow classification	Yes: MAC, IPv4, and IPv6 packets
	Load balancing	Load balancing based on the number of users Load balancing based on user traffic Load balancing based on frequency bands
	Bandwidth limit	Bandwidth limit based on APs Bandwidth limit based on SSIDs
	Call admission control (CAC)	CAC based on the number of users
	Power saving mode	Yes
	Automatic emergency mechanism of APs	Yes
	Intelligent identification of terminals	Yes
Multicast enhancement	Multicast to unicast	
Management	Network management	Centralized management through an AC; both fit and fat modes
	Maintenance mode	Both local and remote maintenance
	Log function	Local logs, Syslog, and log file export
	Alarm	Yes
	Fault detection	Yes

Item	Feature	EAP380-E
	Statistics	Yes
	Switching between the fat and fit modes	An AP working in fit mode can switch to the fat mode through a wireless AC; An AP working in fat mode can switch to the fit mode through a local control port or Telnet.
	Remote probe analysis	Yes
	Dual-image (dual-OS) backup mechanism	Yes
	Watchdog	Yes

Typical Application



SMB office

- Access bandwidth 1167Mbps
- 802.3af PoE
- Ceiling & wall mounting
- Concurrent user 100

Order Information

Product	Description
EAP380-E	DCN SMB Indoor Dual Band AP, 802.11n+802.11ac wave 2 (2.4GHz & 5GHz dual-band, 2*2, bandwidth 1.167Gbps, one 10/100/1000MBase-T port for uplink, PoE or local 48V DC power, default no power adapter), could only be managed by DCN EAC series controller